

MOTORSPORT


SERIE **GE..MTE**
GEH..MTE

MOTORSPORT


SERIE **GE..MTE**
GEH..MTE

MOTORSPORT


SERIE **GE..MTE**
GEH..MTE



GE..MTE



GEH..MTE



ACCIAIO STEEL ACIER	INOX AISI 410
ACCIAIO STEEL ACIER	STAINLESS STEEL INOX AISI 440C
INSERTO ANTIFRIZIONE ANTI-FRICTION LINER COUCHE ANTIFRICTION	

GIOCO PRECARICATO

PRELOADED FIT

JEU PRECHARGE

TIPO TYPE TYPE	Ø B	Ø D	W	H	α	Ø O	carico - load - charge		peso weight poids
							stat.	dynam.	
	H7	0 / -0,013	0 / -0,013	+/- 0,13			kN	kN	g
GE 6 MTE	6	14	6	4	13°	8,0	9	4	4
GE 8 MTE	8	16	8	5	15°	10,2	15,6	7	7
GE 10 MTE	10	19	9	6	12°	13,2	23,4	10	11
GE 12 MTE	12	22	10	7	11°	15,0	32	14	16
GE 15 MTE	15	26	12	9	8°	18,4	50	30	26
GE 16 MTE	16	30	14	10	8°	20,7	65	39	49
GE 17 MTE	17	30	14	10	10°	20,7	65	39	38
GE 20 MTE	20	35	16	12	9°	24,2	90,5	54	61
GE 25 MTE	25	42	20	16	7°	29,3	159	96	110

TIPO TYPE TYPE	Ø B	Ø D	W	H	α	Ø O	carico - load - charge		peso weight poids
							stat.	dynam.	
	H7	0 / -0,013	0 / -0,013	+/- 0,13			kN	kN	g
GEH 12 MTE	12	26	15	9	18°	14,9	50,0	30,0	16
GEH 15 MTE	15	30	16	10	16°	18,4	65,0	39,0	26
GEH 17 MTE	17	35	20	12	19°	20,7	90,5	54,0	38
GEH 20 MTE	20	42	25	16	17°	24,2	159,0	96,0	61

tutte le quote in millimetri - all sizes in millimeters - toutes dimension en millimètres

LUBRIFICAZIONE:

inserto antifrizione con PTFE, rinforzato, senza manutenzione.

LUBRICATION:

reinforced PTFE anti-friction liner, maintenance free.

GRAISSAGE:

couche antifriction avec PTFE, renforcé, sans entretien.

GIOCO:

accoppiamento precaricato, senza gioco.

CLEARANCE:

Preloaded tight fit, no clearance.

JEU:

accouplement serré, sans jeu.

MONTAGGIO:

tabella con interferenza e tolleranza di montaggio disponibile su richiesta.

MOUNTING:

data-sheet with tolerances and fits for mounting available on request.

APPLICATION:

table avec interference et tolérance de montage disponible sur demande.